

Factory-No. 1, No. 64, Shuitou Industrial South Road, Nanhai, Foshan, Guangdong, China Showroom-No. 7, Haiba East Road, Nanhai, Foshan, Guangdong, China

# **CRYSTAL SEAL(WATER-BASED)**

# **DESCRIPTION**

Used for surface treatment of concrete, granite, bricks, sandstone, marble, limestone and other materials

# INSTRUCTIONS FOR USE

- Ensure the stone surface is dry, clean, and free from dust, oil, and other contaminants.
   Maintain adequate ventilation during
- · application.
- Apply evenly using spraying, brushing, or immersion, ensuring complete coverage.
- Apply a sufficient amount to allow for absorption. Coverage: 8-30 m²/L (depending on stone porosity and surface condition).
- Protective effect develops within 5 hours at room temperature. Allow 24 hours for complete curing at room temperature to form a stable hydrophobic layer (optimal protection after 7 days). Protect from rain for 8 hours after application.
- Ideal application temperature: 5°C-35°C (41°F-95°F). Avoid applying to excessively hot surfaces (above 50°C/122°F).
- Shelf life: 3 years in original sealed container.
  Post-shelf-life testing may confirm continued efficacy.

### **FEATURES**

- · Deep penetration
- Stone protection
- Easy to absorb
- Fast penetration
- Fast drying



## STORAGE AND SAFETY

- The storage temperature should be above 0 degrees Celsius and below 45 degrees Celsius.
- No contact with skin/eyes, protective measures recommended.
- Do not take orally, please store in a cool, dry place out of reach of children.

### WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.