

CRYSTAL SEAL (GENERAL TYPE)

DESCRIPTION

This is based on a mixture of silane and siloxane and polymerized with fluorine-containing components. The low surface energy of the fluorine-containing side chain can play a role in preventing oil stains.

Suitable for marble, granite, ceramic.



INSTRUCTIONS FOR USE

- Before construction, clean and dry the stone, keep the construction site well ventilated and fireproof, do not smoke, and do not approach fire.
- The construction temperature should be between 4°C and 45°C. A good water-repellent effect after it is completely dry (generally 24 hours at room temperature), and the best effect is generally more than 7 days in a water-free environment.
- Do not contact with water in 8 hours.
- When applying this product, apply the brush or sponge evenly in a criss-cross pattern without missing any spots. If there is any accumulation of liquid, apply it evenly or absorb it with a cloth.
- Reference dosage: 8-30 square meters/liter. Different types of stone vary due to density, surface conditions and construction methods.
- Please do a small test before stone construction to determine the dosage.

FEATURES

- Contains fluorine. Doubles the protective effect
- Prevents mildew, inhibits the growth of lichens and algae
- Effective prevention of efflorescence

STORAGE AND SAFETY

- The storage temperature should be higher than 0°C and lower than 45°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.