

Factory-No. 1, No. 64, Shuitou Industrial South Road, Nanhai, Foshan, Guangdong, China Showroom-No. 7, Haiba East Road, Nanhai, Foshan, Guangdong, China

MATTE COATING

DESCRIPTION

A solvent-based coating. Suitable for various stone materials such as flamed, bush hammered, honed etc.

INSTRUCTIONS FOR USE

- Clean the floor with an abrasive brush, generally using a sequence of#36-#60-#80-#120 to polish and clean. Use hands to touch and when the surface becomes smooth, it can start applying.
- Clean it with plenty of water, even better with a high-pressure water gun.
- If there is contaminated stone, add detergent according to the conditions, or use other agents to polish/grind and clean it. At the end, be sure to clean and dilute the added agents.
- Apply the first coat when the stone is thoroughly dry and free of dust.
- When applying, increase the brushing force appropriately to effectively clean the residual mud and ash in the low-lying areas, and ensure that the film is clearly attached to every part of the entire surface.
- When applying, separate the construction surface into different parts for operation. The surface of the construction must be evenly applied. If there is no obvious flow on the surface, the next area can be operated. Once there is flow, the thickness will be uneven.
- Control the amount of application at the intersection of the two construction areas, and apply it evenly to avoid uneven application and thickness.
- Touch with your hand to feel the non-stick hand can be painted the second time(generally 25°C above,6 hours later). The longer the interval between the two times, the better.
- Above 25°C, it dries in 12 hours and can be tested with acid. 48 hours later it can be tested for severe destructive properties.



FEATURES

- Acid-proof,alkali-proof,waterproof,oil-proof and UV-resistant.
- The film-forming coating is thin, wear-resistant and does not peel off.
- The nano-level coating does not change the original color and appearance of the stone.

STORAGE AND SAFETY

- The storage temperature should be higher than 0°C and lower than 35°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.