

Factory-No. 1, No. 64, Shuitou Industrial South Road, Nanhai, Foshan, Guangdong, China Showroom-No. 7, Haiba East Road, Nanhai, Foshan, Guangdong, China

1

MARBLE SEAL GLAZE SLURRY

DESCRIPTION

Polishing agent for marble, granite, and artificial stone.

INSTRUCTIONS FOR USE

- Uneven floors and/or gaps or deeply scratched floors must be grinded/polished before by using diamond abrasives. Usually grinded/polished to #1000 and above.
- For stone surfaces with good basic conditions, this product can be used directly.
- Shake the container before each use.
- The surface must be clean, dry and free of any coating.
- Pour a small amount on the stone surface, about 15ml/square meter.
- Use a single-disc polishing machine with steel wool pad to polish. Immediately pass over the machine, left to right and up and down continuously, working 1 to 3 square meters (30-40 square feet), until it is completely dry and bright.
- If necessary, repeat steps 5-6 until the stone surface reaches the required glossiness.

FEATURES

- It can form a dense inorganic transparent armor on the surface of the substrate, and has good bonding and stability on the surface of the material.
- It is a widely applicable substrate protective agent that can reflect the true color of the substrate.



STORAGE AND SAFETY

- The storage temperature should be higher than 0°C and lower than 40°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.