

Factory-No. 1, No. 64, Shuitou Industrial South Road, Nanhai, Foshan, Guangdong, China Showroom-No. 7, Haiba East Road, Nanhai, Foshan, Guangdong, China

N

NANOMETER CRYSTAL FILM

DESCRIPTION

Polishing agent for marble, granite, and artificial stone and ceramic.

INSTRUCTIONS FOR USE

- Uneven floors and/or gaps or deeply scratched floors must be grinded/polished before by using diamond abrasives. Usually grinded/polished to #1000 and above.
- For stone surfaces with good basic conditions, this product can be used directly.
- Shake the container before each use.
- The surface must be clean, dry and free of any coating.
- Pour a small amount on the stone surface, about 15ml/square meter.
- Use a single-disc polishing machine with steel wool pad to polish. Immediately pass over the machine, left to right and up and down continuously, working 1 to 3 square meters (30-40 square feet), until it is completely dry and bright.
- If necessary, repeat steps 5-6 until the stone surface reaches the required glossiness.

FEATURES

- Combines stone hardening, filling and polishing.
- Natural resins and inorganic wearresistant particles penetrate directly into the stone and are blended together to form a highly transparent glossy film layer from the inside out.
- Effectively repairs the cracks and fills the holes in the stone.



STORAGE AND SAFETY

- The storage temperature should be higher than 0°C and lower than 40°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.