

Factory-No. 1, No. 64, Shuitou Industrial South Road, Nanhai, Foshan, Guangdong, China Showroom-No. 7, Haiba East Road, Nanhai, Foshan, Guangdong, China

N

MASTERMASON STONE JOINT FILLER

DESCRIPTION

MASTERMASON STONE JOINT FILLER is a 2-component (A+B) solid glue with excellent resistance to yellowing. It is suitable for filling gaps in floors and walls made of stone, especially for recessed corners and joints.



- Use together with a adjustable hand caulk gun.
- Cut the size of the hose according to the size of the gap that needs to be filled.
- Unscrew the cap and connect the hose to the product.Install this product on the caulk gun.
- Push the caulk gun to squeeze out the mixture until you see that the glue has been evenly mixed and there is no color difference(generally discard the first 30cm of glue)
- Clean the surface and gaps to ensure they are clean and dry.
- Squeeze out the mixture and fill in the gaps.
- Use a professional seam pressing tool to smooth the seams.Pull from one end to the other with a constant force.
- If you want the glue to be at the same level as the surface after curing, you can put painters tape on both sides of the gap. Use a scraper to smooth it after filling the gap. Wait for 5-10 minutes and then tear off the painters tape.
- Wait for 8 hours for it to solidify (above 25 degrees Celsius), the colder the weather, the longer it will take. Use a spatula to clean the remaining glue on the surface.



FEATURES

- · Resistance to yellowing
- Multiple colors availableCan be polished
- Super strong adhesive force
- Anti-vibration
- · Anti-corrosion and oil-resistant

STORAGE AND SAFETY

- The storage temperature should be above 0°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.