

STOVE ANTI-FOULING GLAZE

DESCRIPTION

A film-forming transparent liquid product. It creates a transparent coating that resists contamination from acids, alkalis, soy sauce, etc.

Suitable for surface protection of stone, ceramic tile and quartz.



INSTRUCTIONS FOR USE

- Ensure that the surface to be treated is dry, clean and free of coatings.
- Use 20-30 ml per square.
- Use a clean, lint-free cloth to evenly wipe the liquid.
- Make sure the entire surface is covered.
- It takes 1.5-2 hours for the surface to completely dry. (At 25 °C)
- It takes 5-7 days for the surface to reach the optimal effect. If acid and alkali resistance testing is required, it should be carried out after 7 days. (At 25°C)
- Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

FEATURES

- High gloss and wear resistance
- Acid and alkali resistant
- Usable for indoor and outdoor use
- Long-term maintenance-free

STORAGE AND SAFETY

- The storage temperature should be above 0°C.
- This product is volatile. Use it in a well-ventilated place.
- Wear a mask, goggles and rubber gloves when using it. Avoid causing discomfort to the skin and mucous membranes.
- Do not take orally, store in a cool, dry place out of reach of children and pets.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.