

TERRAZZO CRYSTAL PROTECTION

DESCRIPTION

An epoxy terrazzo nano-silica polishing and antifouling agent. Polishing of all types of artificially laid or prefabricated floors that use epoxy resin as a binder and are made of quartz sand of different particle sizes with or without glass and natural stone.



INSTRUCTIONS FOR USE

- Uneven floors and/or gaps or deeply scratched floors must be grinded/polished before by using diamond abrasives. Usually grinded/polished to #1000 and above.
- For stone surfaces with good basic conditions, this product can be used directly.
- Sprinkle this product on the epoxy terrazzo to be treated, the dosage is 5-10ml/m².
- Use a 175RPM single-disc polishing machine with a 3M 4100 white pad to polish up, down, left, and right until the agent is completely dry and shiny.
- Repeated operations will provide better results.

FEATURES

- Weak alkaline formula
- Anti-fouling
- Wear-resistant
- Brightening
- Simple construction

STORAGE AND SAFETY

- The storage temperature should be higher than 0°C and lower than 35°C.
- Avoid contact with eyes. If it accidentally enters eyes, please rinse with water immediately.
- Do not take orally, please store in a cool, dry place out of reach of children.

WARRANTY

This data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. The application, use or processing of the product is beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.